

**MODEL:** CDS-5085-32-SP | **DESCRIPTION:** SPEAKER**FEATURES**

- 32 Ohm
- rated 0.5 W
- solder pads


**SPECIFICATIONS**

| parameter               | conditions/description  | min  | typ  | max    | units        |
|-------------------------|---|------|------|--------|--------------|
| input power             | max power: 1 minute on, 2 minutes off, 10 cycles              |      | 0.5  | 1.0    | W            |
| impedance               | at 2.0 kHz, 1.0 V   | 27.2 | 32   | 36.8   | $\Omega$     |
| resonant frequency (Fo) | at 1.0 V  | 320  | 400  | 480    | Hz           |
| frequency response      |   | Fo   |      | 20,000 | Hz           |
| sound pressure level    | at 0.1 W, 0.1 m, avg at 0.6, 0.8, 1.0, 1.2 kHz in baffleboard | 89   | 92   | 95     | dB           |
| distortion              | at 1.0 kHz, rated power                                       |      |      | 5      | %            |
| buzz, rattle, etc.      | must be normal at sine wave, between Fo ~ 10,000 Hz           |      |      | 4.0    | V            |
| polarity                | cone moves forward w/ positive dc current to "+" terminal     |      |      |        |              |
| dimensions              | $\varnothing$ 50 x 8.5  |      |      |        | mm           |
| magnet                  | Nd-Fe-B   |      |      |        |              |
| frame material          | SPCC  |      |      |        |              |
| cone material           | PET (black)   |      |      |        |              |
| terminal                | solder pads   |      |      |        |              |
| weight                  |   |      | 13.2 |        | g            |
| operating temperature   |   | -20  |      | 60     | $^{\circ}$ C |
| storage temperature     |   | -30  |      | 70     | $^{\circ}$ C |
| hand soldering          | for maximum 2 seconds   |      |      | 380    | $^{\circ}$ C |
| RoHS                    | yes   |      |      |        |              |


Notes: 1. All specifications measured at 15-35 $^{\circ}$ C, humidity at 45-85%, under 86-106 kPa pressure, unless otherwise noted.

## MECHANICAL DRAWING

units: mm  
tolerance:  $\pm 0.5$  mm



## FREQUENCY RESPONSE CURVE




## PACKAGING


units: mm

Tray QTY: 50 pcs per tray  
 Carton Size: 590 x 300 x 310 mm  
 Carton QTY: 500 pcs per carton



50PCS



50PCS×5=250PCS




250PCS×2=500PCS



TO:

C/N /



|        |                 |
|--------|-----------------|
| MODEL: |                 |
| QTY:   | PCS             |
| N.W:   | kg              |
| G.W:   | kg              |
| SIZE:  | 59 × 30 × 31 cm |
| LOT NO |                 |

## REVISION HISTORY

| rev. | description                  | date       |
|------|------------------------------|------------|
| 1.0  | initial release              | 11/24/2021 |
| 1.01 | logo, datasheet style update | 08/05/2022 |

The revision history provided is for informational purposes only and is believed to be accurate.



CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[cuidevices.com](http://cuidevices.com)