




REV.	DESCRIPTION	DATE
A	NEW DRAWING	5/4/2006



TOLERANCE:  
 X.X ±0.2mm  
 X.XX ±0.1mm  
 X.XXX ±0.05mm



20050 SW 112th Ave.  
 Tualatin, OR 97062  
 Phone: 503-612-2300  
 800-275-4899  
 Fax: 503-612-2383  
 Website: www.cui.com

SPECIFICATIONS:  
 RATING: 24V DC @ 7A  
 INSULATION RESISTANCE: 100M OHMS MIN: 500V DC  
 VOLTAGE WITHSTAND: 500V AC R.M.S. FOR 1 MINUTE  
 LIFE: 5,000 CYCLES  
 OPERATING TEMP: 0° ~ +40°C

TITLE: DC POWER PLUG	REV: A
PART NO: PP-016	UNITS: MM [INCHES]
DRAWN BY: ZRJ	APPROVED BY:
MATERIAL	PLATING
COVER: PE	Black Color
PIN: Brass	Nickel
BARREL: Brass	Nickel
TERMINALS: Brass	Nickel
TIP INSULATOR: PBT	Nickel

PC FILENAME: PP-016

COPYRIGHT 2007 BY CUI INC.

SCALE: 2:1